

MAKING THE BUILDINGS PERFORM

FEATURES

- Versatile Capacitive Touch Switch User Interface for Room Controls
- 1, 2, 3, 4, 5 and 6-button touch input
- Customizable for any application
- Modbus RTU communication
- Customizable icons and texts
- Standard colours black and white
- Standard led colour white off and blue on
- Anti-scratch, Waterproof and easy to clean tampered glass crystal panel
- Versatile applications and uses

TOUCH GLASS SWITCH LX-LC-S8-xBTN-MD

The TOUCH Series LX-LC-S8-xBTN-MD Touch Glass Switches are versatile range of user interface panels for Lonix Modbus Room Controls. Switches have sensitive capacitive touch buttons. This product range brings added value for the user as the sophisticated room control panel with convenient and simple touch input for all room control applications.

VERSATILE USER INTERFACES

The LX-LC-S8-xBTN-MD series switches support a variety of diverse applications and uses. The primary usage of switches is as room panels in hotels, apartments and private homes. Switches work as slaves for LX-BMS-U24-MD unitary controllers. The connectivity with COBA Building Operating System can be done via LX-BMS-NIU & LX-BMS-BIU or any Modbus Bacnet IP converter.

Series has outdoor panels for hotel rooms, door bell units, energy saving card holders and Fan Coil Unit control panels.

LONIX LTD

Hämeentie 153 C, FI-00560 Helsinki, Finland Tel: +358 9 349 9853, www.lonix.com

LX-LC-S8-xBTN-MD

Touch Glass Switches | TOUCH SERIES











TECHNICAL DATA

Operating Voltage: 4-36 VDC **Operating Temperature:** -10 ... 60 °C

Touch buttons: Capacitive high sensitive

Connectivity: Modbus RTU

Modbus settings: No parity, 8 data bits, 1 stop bit, speed

4800/9600/19200/38000 bps

Settings: Modbus address, baud rate, button and

led function

Led Colour: White (faint) Off, Blue On

IP Class: IP20

Dimensions: 86 (w) x 86 (h) x 45 (d) mm

Mounting: Standard IEC 60670-1 pattress box of

68 (60) mm (3" by 3" box)

EMC Standards: Compliance according to EN 55022, EN

61000-4-3, EN 61000-4-5

Production Standards: ISO-9001, ISO-14001

ORDER CODE: LX-LC-S8-1BTN-MD white

LX-LC-S8-2BTN-MD white LX-LC-S8-3BTN-MD black LX-LC-S8-4BTN-MD black LX-LC-S8-5BTN-MD black LX-LC-S8-6BTN-MD black